



DOT-N23-G STAIR NOSING

Introducing Dottac's N23G-A & N23G-C Stair Nosing, a durable and robust aluminium structure designed to withstand high-traffic environments. The carborundum insert surpasses the Australian Standards for anti-slip surfaces, ensuring optimal safety. The N23 nosing can be installed in various ways, including fixing adhesive on multiple surfaces like concrete, timber, tiles, and carpets, making it a versatile option for both interior and exterior applications.

SLIP RESISTANCE

Important information: To determine a classification of a slip resistance rating, see Australian Standards AS 4586: 2004 Slip Resistance Classification of New Pedestrian Surface Materials.


TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= AI = 48 = Carb = 66
TRL 55 SLIDER	= AI = 49 = Carb = 86

TEST	AS 4586 APPENDIX B: Dry Floor Friction Test
MEAN COF	= AI = 0.60 = D1 = Carb = 0.80 = D1

LUMINANCE TESTING

Luminance contrast requirement of the National Construction Code (NCC) 3.2 and the AS/NZ 1428.4.2002

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3
ALUMINIUM	
LUMINANCE REFLECTANCE RATING / WET	= 2.9
LUMINANCE REFLECTANCE RATING / DRY	= 3.2
CARBORUNDUM	
LUMINANCE REFLECTANCE RATING / WET	= 3.2
LUMINANCE REFLECTANCE RATING / DRY	= 3.5



PRODUCT	Extrusion Profile Stair Nosing
MATERIAL	Gold Aluminium
FINISH	Mill Finish
Size	75mm x10mm
INSERT	Black Solid Carborundum or Aluminium
FIXING	Adhesive



DOTTAC
 ABN: 42 153 893 933
 Registered Address:
 14 Kirke Street
 Balcatta WA 6021

T: 0423 418 168
 info@dottac.com.au
 admin@dottac.com.au
www.dottac.com.au