



DOT-N31 ANTI-SLIP TAPE

Dottac N31 Anti-Slip Tape is a robust solution tailored for high foot traffic zones in all listed indoor surfaces. The Carborundum tape surpasses beyond the Australian Standards and measures 53mm wide and comes in a roll of 18.2 m long. It is fabricated from sturdy carbide anti-slip grit and is available in both black and yellow.

SLIP RESISTANCE

Important information: To determine a classification of a slip resistance rating, see Australian Standards AS 4586: 2004 Slip Resistance Classification of New Pedestrian Surface Materials.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= Yellow = 70 = Black = 70
TRL 55 SLIDER	= Yellow = 81 = Black = 76
TEST	AS 4586 APPENDIX B: Dry Floor Friction Test
MEAN COF	= Yellow = 0.90 = D1 = Black = 0.85 = D1

LUMINANCE TESTING

Luminance contrast requirement of the National Construction Code (NCC) 3.2 and the AS/NZ 1428.4.2002

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3
YELLOW	
LUMINANCE REFLECTANCE RATING / WET	= 36.7
LUMINANCE REFLECTANCE RATING / DRY	= 38.2
BLACK	
LUMINANCE REFLECTANCE RATING / WET	= 3.9
LUMINANCE REFLECTANCE RATING / DRY	= 5.3

PRODUCT	Anti-slip Carborundum Tape
MATERIAL	Carborundum Tape with 80 Grit Silicon Carbide
FINISH	Yellow or Black
SIZE	53mm x 18.2 M



DOTTAC
 ABN: 42 153 893 933
 Registered Address:
 14 Kirke Street
 Balcatta WA 6021

T:08 6384 6349
info@dottac.com.au
admin@dottac.com.au
www.dottac.com.au