



# DOT-N24-C STAIR NOSING

Dottac N24 Stair Nosing is a robust and durable solution tailored for high foot traffic zones. Reinforced aluminium construction guarantees longevity and endurance under heavy usage. The anodised aluminium profiles are 18-20 microns in thickness. Setting apart from the other N24 range is the carborundum insert, which surpasses beyond the Australian Standards. It measures at 50mm wide and is extruded from 6063/T5 grade aluminium, and is design for both internal and external use.

## SLIP RESISTANCE

Important information: To determine a classification of a slip resistance rating, see Australian Standards AS 4586: 2004 Slip Resistance Classification of New Pedestrian Surface Materials.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= Black = 66 = Yellow = 66
TRL 55 SLIDER	= Black = 69 = Yellow = 86


TEST	AS 4586 APPENDIX B: Dry Floor Friction Test
MEAN COF	= Black = 0.80 = D1 = Yellow = 0.85 = D1

## LUMINANCE TESTING

Luminance contrast requirement of the National Construction Code (NCC ) 3.2 and the AS/NZ 1428.4.2002

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3
BLACK	
LUMINANCE REFLECTANCE RATING / WET	= 2.9
LUMINANCE REFLECTANCE RATING / DRY	= 3.2
YELLOW	
LUMINANCE REFLECTANCE RATING / WET	= 30.6
LUMINANCE REFLECTANCE RATING / DRY	= 32.2

<b>PRODUCT</b>	Extrusion Profile Stair Nosing
<b>MATERIAL</b>	Clear or Gold Aluminium
<b>FINISH</b>	Mill Finish
<b>INSERT</b>	Black or Yellow Carborundum
<b>FIXING</b>	Screw and Glue OR Glue



**DOTTAC**  
 ABN: 42 153 893 933  
 Registered Address:  
 14 Kirke Street  
 Balcatta WA 6021

T: 0423 418 168  
[info@dottac.com.au](mailto:info@dottac.com.au)  
[admin@dottac.com.au](mailto:admin@dottac.com.au)  
[www.dottac.com.au](http://www.dottac.com.au)