

DOT0012 WARNING TACTILE

Dottac Stainless Steel Warning Tactile with a Carborundum Insert (DOT0012) is a high-quality, slip-resistant solution made from 316 marine grade stainless steel. Its carborundum insert design provides an excellent grip while the smooth outer edge ensures safety for all users. It's ideal for both outdoor and indoor environments, it is resistant to corrosion and easy to install and maintain. Compliant with Australian Standards, it is suitable for public spaces, transportation hubs, and commercial buildings.

FEATURES

Machined, with carborundum insert design on the horizontal face, with a smooth outer edge

Tested for compliance with AS 1428.4

Tested for compliance with the NCC Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 198

<u>Substrates</u>: Stone, Masonry, Timber, Vinyl, Carpet Tile, Porcelain, Ceramic, Glass Material

WARRANTY 5-year warranty on the product

SLIP RESISTANCE

Important information: To determine a classification of a slip resistance rating, see Australian Standards AS 4586: 2004 Slip Resistance Classification of New Pedestrian Surface Materials.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test	
FOUR S 96 SLIDER	= 59 CLASS = P5	
TRL 55 SLIDER	= 54 CLASS = P5	
TEST	AS 4586 APPENDIX C: Wet/Barefoot Ramp Test	
MEAN ANGLE OF INCLINATION	= 37° CLASS = C	
TEST	AS 4586 APPENDIX D: Oil/Wet Ramp Test	
CORRECTED MEAN OVERALL ACCEPTANCE ANGLE = 15.8° CLASS		


LUMINANCE TESTING

Luminance contrast requirement of the National Construction Code (NCC) 3.2 and the AS/NZ 1428.4.2002

TEST	AS/NZS 1428.4.1 A	PPENDIX E PARAGRAPH E3
LUMINANCE REFLECTANCE RATING / WET = 4		= 4.73
LUMINANCE REFLECTANCE RATING / DRY =		= 6.87

ТҮРЕ	Stainless Steel with Carborundum Insert
MATERIAL	316 Marine Grade
FINISH	Machined / Cast
FIXING	Core Drill and Pressure Fit
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm







DOTTAC

ABN: 42 153 893 933

Registered Address: 14 Kirke Street Balcatta WA 6021 T: O423 418 168 info@dottac.com.au admin@dottac.com.au www.dottac.com.au