



DOT0105 INTEGRATED TACTILE

Dottac Polyurethane Warning Tactile (DOT0105) is a high-quality, slip-resistant solution made from Polyurethane. Its concentric groove design provides an excellent product that ensures safety for all users. It's ideal for both outdoor and indoor environments, it is resistant to corrosion and easy to install and maintain. Compliant with Australian Standards, it is suitable for public spaces, transportation hubs, and commercial buildings.

FEATURES

Machined, with concentric circle design on the horizontal face with a smooth outer edge

Tested for compliance with AS 1428.4

Tested for compliance with the NCC Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 198

Substrates: Stone, Masonry, Timber, Vinyl, Carpet Tile, Porcelain, Ceramic, Glass Material

WARRANTY 2 years warranty on the product

SLIP RESISTANCE

Important information: To determine a classification of a slip resistance rating, see Australian Standards AS 4586: 2004 Slip Resistance Classification of New Pedestrian Surface Materials.


TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 59 CLASS= P5
TRL 55 SLIDER	=59 CLASS =P5

LUMINANCE TESTING

Luminance contrast requirement of the National Construction Code (NCC) 3.2 and the AS/NZ 1428.4.2002

TEST	AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3
LUMINANCE REFLECTANCE RATING / WET	= 4.0
LUMINANCE REFLECTANCE RATING / DRY	= 4.1

TYPE	Polyurethane
MATERIAL	Black Polyurethane
FINISH	Injection Moulded
FIXING	Adhesive
DIMENSIONS	300 x 300mm



DOTTAC
ABN: 42 153 893 933
Registered Address:
14 Kirke Street
Balcatta WA 6021

T: 0423 418 168
info@dottac.com.au
admin@dottac.com.au
www.dottac.com.au