

DOT0106 INTEGRATED TACTILE

TYPE

FINISH

FIXING

DIMENSIONS

MATERIAL

Dottac Polyurethane Warning Tactile (DOT0106) is a high-quality, slip-resistant solution made from Polyurethane Its concentric groove design provides an excellent product ensures safety for all users. It's ideal for both outdoor and indoor environments, it is resistant to corrosion and easy to install and maintain. Compliant with Australian Standards, it is suitable for public spaces, transportation hubs, and commercial buildings.

Polyurethane

Adhersive

300 x 300mm

Grey Polyurethane

Injection Moulded

FEATURES

Machined, with concentric circle design on the horizontal face with a smooth outer edge

Tested for compliance with AS 1428.4

Tested for compliance with the NCC Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 198

<u>Substrates</u>: Stone, Masonry, Timber, Vinyl, Carpet Tile, Porcelain, Ceramic, Glass Material

WARRANTY 2 yearsr warranty on the product

SLIP RESISTANCE

Important information: To determine a classification of a slip resistance rating, see Australian Standards AS 4586: 2004 Slip Resistance Classification of New Pedestrian Surface Materials.

TEOT	AO 4500 ARRENDIVA IN ART TO
TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	54 CLASS =P4
TRL 55 SLIDER	68 CLASS =P5

LUMINANCE TESTING

Luminance contrast requirement of the National Construction Code (NCC) 3.2 and the AS/NZ 1428.4.2002

TEST	AS/NZS 1428.4.1 APPENDIX E PAR	AGRAPH E3
LUMINANCE REFLECTANCE RATING / WET		43.7
LUMINANCE REFLECTANCE RATING /	DRY	44.4



DOTTAC

ABN: 42 153 893 933

Registered Address: 14 Kirke Street Balcatta WA 6021 T: 0423 418 168 info@dottac.com.au admin@dottac.com.au www.dottac.com.au